



LifeKeeper[®] for Linux v5.0

Sybase ASE Recovery Kit
Administration Guide

October 2010

SteelEye and LifeKeeper are registered trademarks.

Adobe Acrobat is a registered trademark of Adobe Systems Incorporation. Apache is a trademark of The Apache Software Foundation. HP and Compaq are registered trademarks of Hewlett-Packard Company. IBM, POWER, DB2, Informix, ServeRAID, Rational and ClearCase are registered trademarks or trademarks of International Business Machines Corporation. Intel, Itanium, Pentium and Xeon are registered trademarks of Intel Corporation. Java is a registered trademark of Sun Microsystems, Inc. Linux is a registered trademark of Linus Torvalds. Microsoft Internet Explorer and Windows are registered trademarks of Microsoft Corporation. MySQL and MaxDB are registered trademarks or trademarks of MySQL AB. Netscape and Netscape Navigator are registered trademarks of Netscape Communications Corporation. NFS is a registered trademark of Sun Microsystems, Inc. Opteron is a trademark of Advanced Micro Devices, Inc. Oracle is a registered trademark of Oracle Corporation and/or its affiliates. PostgreSQL is a trademark of PostgreSQL Global Development Group. Red Flag is a registered trademark of Red Flag Software Co.,Ltd. Red Hat is a registered trademark of Red Hat Software, Inc. SAP is a registered trademark of SAP AG. Sendmail is a registered trademark of Sendmail, Inc. Sun and Solaris are registered trademarks of Sun Microsystems, Inc. SUSE is a registered trademark of SUSE LINUX AG, a Novell business. Sybase is a registered trademark of Sybase, Inc. Other brand and product names used herein are for identification purposes only and may be trademarks of their respective companies.

It is the policy of SIOS Technology Corp. (previously known as SteelEye Technology, Inc.) to improve products as new technology, components, software and firm-ware become available. SIOS Technology Corp., therefore, reserves the right to change specifications without prior notice.

To maintain the quality of our publications, we need your comments on the accuracy, clarity, organization and value of this book.

Address correspondence to:
ip@us.sios.com

Copyright © 2010
By SIOS Technology Corp.
San Mateo, CA U.S.A.
All Rights Reserved

Table of Contents

Introduction.....	3
Document Contents	3
LifeKeeper Documentation	4
Sybase ASE Documentation.....	4
Sybase ASE 12.5	4
Sybase ASE Recovery Kit Requirements	5
Hardware Requirements.....	5
Software Requirements.....	5
Overview.....	6
Sybase ASE Resource Hierarchy.....	6
Configuration Considerations.....	8
Using Raw I/O.....	8
Using Mirrored File Systems with LKDR.....	8
Interfaces File Considerations	8
Sybase Software Asset Manager (SySAM).....	9
Active/Standby Considerations	9
Scenario 1.....	9
Scenario 2.....	10
Active/Active Considerations.....	10
Scenario 1.....	11
Scenario 2.....	11
Sybase Monitor Server and Backup Server Considerations	12
Configuring Sybase ASE with LifeKeeper	13
Install the Sybase ASE Software	13
Create the Sybase ASE Servers	13
Install the LifeKeeper Software.....	14
Resource Configuration Tasks	15
Creating a Sybase ASE Resource Hierarchy	16
Extending a Sybase ASE Resource Hierarchy.....	18
Unextending a Sybase ASE Resource Hierarchy.....	19
Deleting a Sybase ASE Resource Hierarchy	19
Testing Your Resource Hierarchy	20
Performing a Manual Switchover from the LifeKeeper GUI	20
Resource Hierarchy Administration	21
Modifying protection for the Sybase Backup Server	21
Adding a Sybase Backup Server.....	21
Removing a Sybase Backup Server	22
Modifying Protection for the Sybase Monitor Server	22
Adding a Sybase Monitor Server.....	22
Removing a Sybase Monitor Server.....	23
Updating Parameters.....	24
Troubleshooting	25
Sybase ASE Recovery Kit Error Messages.....	25
Appendix.....	27
Creating Device Spaces using Raw I/O	27
Requirements.....	27
Naming Conventions.....	27
Raw I/O Setup Steps	27

Adding a Device Space after Creating Hierarchy.....	28
Creating Links for ASE and OCS.....	28

Sybase ASE Recovery Kit Administration Guide

Introduction

Sybase Adaptive Server Enterprise is a powerful data management platform for high performance business applications. Sybase ASE is a versatile, enterprise-class RDBMS that is especially good at handling OLTP workloads. Sybase ASE is used widely in financial, E-commerce, and other technology arenas. The Sybase ASE platform includes many standard components, such as the Adaptive Server, Monitor Server, and Backup Server, as well as other plug-in components. The Adaptive Server component is the relational database server. The Monitor Server is a separate server from the database server that monitors the Adaptive Server. The Monitor Server can provide real time or historical data to client applications. The Backup Server is an Open Server-based application that manages all database backup (dump) and restore (load) operations for Adaptive Server.

The Sybase ASE Recovery Kit will provide LifeKeeper resource protection for the Sybase ASE components Adaptive Server, Monitor Server, and Backup Server.

Document Contents

This guide includes the following topics to help you successfully define and manage your Sybase ASE hierarchy:

- [Sybase ASE Recovery Kit Requirements](#). Lists the hardware and software necessary to properly setup, install and operate the Sybase ASE Recovery Kit.
- [Overview](#). Describes the Sybase ASE Recovery Kit's features and functionality.
- [Configuration Considerations](#). Contains information to consider before you install and configure the Sybase ASE Recovery Kit.
- [Configuring Sybase ASE with LifeKeeper](#). Provides instructions for installing and configuring the Sybase ASE software and LifeKeeper software.
- [Resource Configuration Tasks](#). Describes the various functions you may perform on your hierarchies using the LifeKeeper GUI: create, extend, delete, and unextend.
- [Hierarchy Administration](#). Provides important recommendations for ongoing administration of the Sybase ASE hierarchy.
- [Troubleshooting](#). Lists and describes the error messages associated with the Sybase ASE Recovery Kit.
- [Appendix](#). Provides requirements and instructions for setting up raw devices for use with the Sybase ASE Recovery Kit. Provides instructions and examples for verifying additional Sybase installation requirements.

LifeKeeper Documentation

The following documentation is associated with the LifeKeeper Core:

- *Release Notes*
- *Online Product Manual*
- *Planning and Installation Guide*

This documentation, along with documentation associated with other LifeKeeper Recovery Kits, is available online at <http://us.sios.com/support>. The *Online Product Manual* is also available from the Help menu in the LifeKeeper GUI.

Sybase ASE Documentation

You can find Sybase ASE documentation, including the *Installation Guide Adaptive Server for Linux*, *User Manual*, *Monitor Server User Manual*, *Troubleshooting Guide* and *Reference Manual(s)* at the following location on the web:

Sybase ASE 12.5

<http://sybooks.sybase.com/onlinebooks/group-as/asg1251e>

Sybase ASE Recovery Kit Requirements

Your LifeKeeper configuration must meet the following requirements prior to the installation of LifeKeeper for Linux Sybase Recovery Kit. Please see the *LifeKeeper for Linux Planning and Installation Guide* for specific instructions regarding the installation and configuration of your LifeKeeper hardware and software.

Hardware Requirements

- **Servers** - Servers should be configured in accordance with the requirements described in the *LifeKeeper for Linux Planning and Installation Guide* and the *LifeKeeper for Linux Release Notes*.
- **IP Network Interface Cards** - Each server requires at least one Ethernet TCP/IP-supported network interface card. Remember, however, that a LifeKeeper cluster requires at least two communications paths. Two separate LAN-based communication paths using dual independent sub-nets are recommended for heartbeats, and at least one of these should be configured as a private network. Using a combination of TCP and TTY heartbeats is also supported.
- **Storage** – Servers should be configured to use LifeKeeper supported shared storage, or the LifeKeeper for Linux Data Replication storage.

Software Requirements


- TCP/IP Software – Each server in your LifeKeeper configuration requires TCP/IP Software.
- Sybase ASE Software – LifeKeeper supports version 12.5 (12.5.0.1 and 12.5.1) of the Sybase ASE software. This version can be obtained from Sybase Inc. at <http://www.sybase.com/products/databaseservers/ase>. **Note:** The same version of the Sybase ASE software **must** be installed on all servers in the cluster. In addition, only one version of the Sybase ASE software may be installed on the LifeKeeper protected servers.
- LifeKeeper software – It is imperative that you install the same version of the LifeKeeper software and apply the same versions of the LifeKeeper software patches to each server in your cluster.
- LifeKeeper for Linux IP Recovery Kit – The LifeKeeper for Linux IP Recovery Kit is required by the LifeKeeper for Linux Sybase ASE Recovery Kit. The LifeKeeper for Linux IP Recovery Kit is provided on the LifeKeeper for Linux Core CD.
- LifeKeeper for Linux Sybase ASE Recovery Kit – The Sybase ASE Recovery Kit is provided on a CD. It is packaged, installed and removed via Red Hat Package Manager, rpm. The following rpm file is supplied on the LifeKeeper for Linux Sybase ASE Recovery Kit CD:
steeleye-lkSYBASE

Overview

The LifeKeeper for Linux Sybase ASE Recovery Kit provides a mechanism for protecting Sybase ASE Server instances within LifeKeeper. The Sybase ASE software, LifeKeeper Core and Sybase ASE Recovery Kit are installed on two or more servers in a cluster. Once the Sybase ASE Server instance is under LifeKeeper protection, clients connect to the database using a LifeKeeper protected IP address. The LifeKeeper protected IP address must be created separately prior to the creation of the Sybase ASE resource hierarchy. The Sybase ASE resource hierarchy creation will create the dependency between the parent Sybase ASE resource instance, and the child IP address resource. In the event that the Sybase ASE Server instance fails, LifeKeeper will first attempt to recover it on the local server. If the local recovery fails, then LifeKeeper will fail over to a backup server.

Sybase ASE Resource Hierarchy

The following example shows an example Sybase ASE resource hierarchy:



The dependencies in the above example correspond to the following protected resources:

Resource	Sybase ASE Software Component
LKIP.EXAMPLE.COM	Protects the switchable IP address used for client connections
sybase/config	Protects the file system containing the Sybase Adaptive Server, Monitor Server, and Backup Server configuration files
sybase/master	Protects the Sybase ASE master device
sybase/shm	Protects the Sybase Adaptive Server, and Monitor Server shared memory path
sybase/sybsystemdb	Protects the Sybase ASE sybsystemdb device
sybase/sybsystemprocs	Protects the Sybase ASE sybsystemprocs device

In the event of failover, LifeKeeper will bring the file system, IP address and database resources (including all the resource dependencies) in service on a backup server. Clients will be disconnected, and will need to re-connect to the server. Any SQL statement that has not been committed will need to be re-entered.

Configuration Considerations

This section contains information that you should consider before you start to configure and administer the Sybase ASE Recovery Kit.


Using Raw I/O

If you plan to use Sybase ASE with raw devices, you must install the LifeKeeper Raw I/O Recovery Kit from the LifeKeeper Core CD. You must also properly set up the raw I/O devices prior to use. See the [Appendix](#) for instructions.

Using Mirrored File Systems with LKDR

The Sybase ASE Recovery Kit supports the use of LifeKeeper Data Replication (LKDR) as a device space. In addition, the Sybase ASE software can be installed on mirrored file systems.

For example, a dependent file system for a Sybase ASE resource would look similar to the following, which shows a file system for the system device space and its dependency, the LKDR resource mirror.



Interfaces File Considerations

The Sybase ASE Recovery Kit uses the Sybase ASE interfaces file for the detection of the client IP addresses and ports. This file is located under \$\$SYBASE, and is typically called interfaces. This file is updated whenever an Adaptive Server, Monitor Server, or Backup Server instance is created using the srvbuid or similar configuration utility. The LifeKeeper for Linux Sybase ASE Recovery Kit requires this file to exist with entries for each Sybase ASE component to be protected. Comment lines are not allowed. All server names that appear in the interfaces file must be resolvable to a valid virtual IP address. All servers that will protect the Sybase ASE resource hierarchy must be able to resolve the server names that appear in the interfaces file. In addition, it is recommended that the virtual IP address be used instead of the server name.

Example

```
master tcp ether example.com 4100
```

```
query tcp ether example.com 4100
```

Example_back

```
master tcp ether example.com 4200
```

```
query tcp ether example.com 4200
```

Example_mon

```
master tcp ether example.com 4200
```

```
query tcp ether example.com 4200
```

Sample Interfaces file

Sybase Software Asset Manager (SySAM)

The Sybase Software Asset Management (SySAM) is used to manage licensed Sybase products. At Sybase ASE server startup, each ASE server component checks the license file in its environment for permission to run specific features. In order for the ASE server to do this, a license manager and vendor module must be running. The LifeKeeper for Linux Sybase ASE Recovery Kit does not provide protection for the SySAM license manager. It is recommended that the license manager be configured in a redundant server system. In the redundant server system, the redundant license allows you to specify local servers as the first license server in the queue, and make remote servers available as backup license servers. The SySAM application attempts to check out a license from a license-file list, starting with the first server. If that server fails for any reason, the second server in the list is contacted, and so on. The `LM_LICENSE_FILE` variable must be set properly in the user profile for the redundant license server environment.

Active/Standby Considerations

In an Active/Standby configuration the backup server is not actively running the Sybase ASE, but stands by in case the primary server experiences a failure. The following scenarios provide specific requirements that must be adhered to when protecting a Sybase ASE resource instance in active/standby configurations.

Scenario 1

The Sybase ASE product is installed **locally on all servers in the cluster**.

- All Sybase Adaptive Server, Monitor Server, and Backup Server devices are configured on shared storage.

- The Sybase Adaptive Server, Monitor Server, and Backup Server configuration files are stored on a shared file system.
- The Sybase Adaptive Server and Monitor Server shared memory directory is located on a shared file system.
- The interfaces file must be manually updated on all servers to contain common entries for each instance to be protected.
- All interfaces file entries must be resolvable by all servers where the resource will be protected
- The RUN files for each Adaptive Server, Monitor Server, and Backup Server must exist on all servers in the cluster.
- The RUN files for each Adaptive Server, Monitor Server, and Backup Server must be executable on all servers in the cluster.
- The RUN files for each Adaptive Server, Monitor Server, and Backup Server must contain the same options on all servers in the cluster.

Scenario 2

The Sybase ASE product is installed to **one or more shared file systems on the primary server.**

- All Sybase Adaptive Server, Monitor Server, and Backup Server devices are configured on shared storage.
- The Sybase Adaptive Server, Monitor Server, and Backup Server configuration files are stored on a shared file system
- The Sybase Adaptive Server and Monitor Server shared memory directory is located on a shared file system
- The interfaces file does not have to be updated on the target servers
- All interfaces file entries must be resolvable by all servers where the resource will be protected
- On the LifeKeeper backup server `/etc/ld.so.conf` must be updated to add entries for the Sybase product libraries
 - Add an entry for `$$SYBASE/ASE/lib`
 - Add an entry for `SYBASE/OCS/lib`
 - Mount the shared file system containing the Sybase ASE installed products and run `ldconfig`

Active/Active Considerations

In an Active/Active configuration, each server is actively running one or more Sybase ASE Servers, while acting as a backup for the other LifeKeeper server in case of failure. The following scenario provides specific requirements that must be adhered to in sequential order when protecting a Sybase ASE resource instance in an active/active configuration.

Scenario1

The Sybase ASE product is installed **locally on all servers in the cluster**.

- All Sybase Adaptive Server, Monitor Server, and Backup Server devices are configured on shared storage.
- The Sybase Adaptive Server, Monitor Server, and Backup Server configuration files are stored on a shared file system.
- The Sybase Adaptive Server and Monitor Server shared memory directory is located on a shared file system.
- The interfaces file must be manually updated on all servers to contain common entries for each instance to be protected
- All interfaces file entries must be resolvable by all servers where the resource will be protected
- The RUN files for each Adaptive Server, Monitor Server, and Backup Server must exist on all servers in the cluster.
- The RUN files for each Adaptive Server, Monitor Server, and Backup Server must be executable on all servers in the cluster.
- The RUN files for each Adaptive Server, Monitor Server, and Backup Server must contain the same options on all servers in the cluster.

Scenario 2

The Sybase ASE product is installed to **one or more shared file systems on the primary server**.

- All Sybase Adaptive Server, Monitor Server, and Backup Server devices are configured on shared storage.
- The Sybase Adaptive Server, Monitor Server, and Backup Server configuration files are stored on a shared file system
- The Sybase Adaptive Server and Monitor Server shared memory directory is located on a shared file system
- The interfaces file does not have to be updated on the target servers
- All interfaces file entries must be resolvable by all servers where the resource will be protected
- On the LifeKeeper backup server `/etc/ld.so.conf` must be updated to add entries for the Sybase product libraries
 - Add an entry for `$SYBASE/ASE/lib`
 - Add an entry for `SYBASE/OCS/lib`
 - Mount the shared file system containing the Sybase ASE installed products and run `ldconfig`

Sybase Monitor Server and Backup Server Considerations

The LifeKeeper for Linux Sybase ASE recovery kit provides resource protection for the Adaptive Server, Backup Server, and Monitor Server components. However, the Backup Server and Monitor Server components are not required components of a resource hierarchy. The Sybase Backup Server, and the Sybase Monitor Server can be excluded from the resource protection. During the resource hierarchy creation users that do not wish to protect the Sybase Monitor Server, and/or the Sybase Backup Server can choose none for the respective component choices. Selecting none during the GUI resource creation will exclude the selected component from protection in the resource hierarchy. **Note:** 'none' is a reserved word in the Sybase ASE Recovery Kit, therefore neither the Sybase Backup Server nor the Sybase Monitor Server can be named 'none'.

When choosing whether to protect these components it is important to note that the configuration files that share a common file system with the Adaptive Server configuration files, device paths, log paths, or shared memory directories will be protected by LifeKeeper. If one or more components will not be protected with LifeKeeper, considerations for file placement should be made to prevent sharing between the protected components and the non-protected components.

Configuring Sybase ASE with LifeKeeper

The following sequence is recommended for installing and configuring the Sybase ASE product and LifeKeeper software. Each of these steps links to detailed tasks that follow.

1. [Install the Sybase ASE software.](#)
2. [Create the Sybase ASE Server\(s\).](#)
3. [Install the LifeKeeper Core and Sybase ASE Recovery Kit.](#)

After you have performed these tasks, you will be ready to create the LifeKeeper resource hierarchy to protect your Sybase ASE Server(s).

Install the Sybase ASE Software

Install the Sybase ASE software on all servers in the cluster using **identical** parameters/settings. Refer to the *Installation Guide Adaptive Server for Linux* for details. The following are additional recommendations to ensure that LifeKeeper will work with Sybase ASE:

- A non-root system user (Sybase OS User) must exist on all servers. The user must have the same user id, group id, and home directory on all servers where the resource(s) will be protected.
- The Sybase ASE common software packages must be installed. This package provides both the Sybase srbuild and Sybase isql utilities.
- Each LifeKeeper server containing a Sybase ASE resource hierarchy must have identical service entries in the `$$SYBASE/interfaces` file for the Sybase ASE Server(s).
- Verify that a link exists between `$$SYBASE/ASE-<version>` and `$$SYBASE/ASE`. If the link does not exist, it must be manually created. See the [Appendix](#) for additional information.
- Verify that a link exists between `$$SYBASE/OCS-<version>` and `$$SYBASE/OCS`. If the link does not exist, it must be manually created. See the [Appendix](#) for additional information.
- Refer to the *Installation Guide Adaptive Server for Linux* for details on configuring shared memory parameters for the Adaptive Server, Monitor Server, and Backup Server.

Create the Sybase ASE Servers

Follow the instructions in your *Installation Guide Adaptive Server for Linux* for configuring the Sybase Adaptive Server, Monitor Server, and Backup Server. The following considerations should be followed:

- Use the srbuild utility or other Sybase ASE utility to create the Sybase Adaptive Server instance
 - Configure all system devices on shared storage
 - Configure the Adaptive Server configuration files on shared storage
 - Configure the Adaptive Server shared memory directory on shared storage
 - Configure the interface to use a LifeKeeper switch-able IP address
 - Optionally configure the logs on shared storage

- If required, create the Sybase Monitor Server instance
 - Configure all system devices on shared storage
 - Configure the Monitor Server configuration files on shared storage
 - Configure the Monitor Server shared memory directory on shared storage
 - Configure the interface to use a LifeKeeper switch-able IP address
 - Optionally configure the logs on shared storage
- If required, create the Sybase Backup Server instance
 - Configure all system devices on shared storage
 - Configure the Monitor Server configuration files on shared storage
 - Configure the Monitor Server shared memory directory on shared storage
 - Configure the interface to use a LifeKeeper switch-able IP address
 - Optionally configure the logs on shared storage

Install the LifeKeeper Software

Once you have installed the Sybase ASE software, and created your database servers, you are ready to install the LifeKeeper Core software, LifeKeeper for Linux IP Recovery Kit, and any required patches, followed by the Sybase ASE Recovery Kit. Also, if you plan to use Sybase ASE with raw devices, you must install the LifeKeeper Raw I/O Recovery Kit from the LifeKeeper Core CD. See the [Appendix](#) for requirements and instructions on setting up raw devices.

Refer to the *LifeKeeper for Linux Planning and Installation Guide* for details on installing the LifeKeeper packages.

Resource Configuration Tasks

Once you have completed the setup tasks described in the previous section, you are ready to create and extend your Sybase ASE resource hierarchies.

The following tasks are available for configuring the LifeKeeper for Linux Sybase ASE Recovery Kit:

- **Create Resource Hierarchy** - Creates a Sybase ASE resource hierarchy
- **Delete Resource Hierarchy** - Deletes a Sybase ASE resource hierarchy
- **Extend Resource Hierarchy** - Extends a Sybase ASE resource hierarchy from the primary server to the backup server.
- **Unextend Resource Hierarchy** - Unextends (removes) a Sybase ASE resource hierarchy from a single server in the LifeKeeper cluster.

Refer to the GUI Administrative Tasks section of *LifeKeeper Online Product Manual* for instructions on configuring LifeKeeper Core resource hierarchies, for instance, file system and IP resources.

In addition, refer to the *LifeKeeper Online Product Manual* for details on the following because they are common tasks with steps that are identical across all recovery kits.

- **Create Dependency** - Creates a child dependency between an existing resource hierarchy and another resource instance and propagates the dependency changes to all applicable servers in the cluster.
- **Delete Dependency** - Deletes a resource dependency and propagates the dependency changes to all applicable servers in the cluster.
- **In Service** - Activates a resource hierarchy.
- **Out of Service** - Deactivates a resource hierarchy.
- **View/Edit Properties** - View or edit the properties of a resource hierarchy.

Note: Throughout the rest of this section, configuration tasks are performed using the **Edit** menu. You may also perform most of the tasks:


- from the toolbar
- by right-clicking on a global resource in the left pane of the status display
- by right-clicking on a resource in the right pane of the status display

Using the right-click method allows you to avoid entering information that is required using the **Edit** menu.

Creating a Sybase ASE Resource Hierarchy

Perform the following steps on the primary server:

1. On the **Edit** menu, select **Server**, then **Create Resource Hierarchy**.



The *Create Resource Wizard* dialog will appear.

2. Select Sybase ASE Database from the drop down list and click **Next**.
3. You will be prompted for the following information. When the **Back** button is active in any of the dialog boxes, you can go back to the previous dialog box. This is helpful should you encounter any error requiring you to correct the previously entered information. You may click **Cancel** at any time to cancel the entire creation process.

Field	Tips
Server	Select the LifeKeeper server where the Sybase ASE resource is to be created.
Switchback Type	Choose either intelligent or automatic. This determines how the Sybase ASE resource will be switched back to the primary server after it comes in-service (active) on the backup server following a failover. Intelligent switchback requires administrative intervention to switch the resource back to the primary server, while automatic switchback occurs as soon as the primary server is back on line and reestablishes LifeKeeper communication paths. Note: The switchback strategy must match that of the dependent resources to be used by the Sybase ASE resource.
Sybase Install Directory	The field is used to specify the installation location of the Sybase ASE product. You may type in another directory path. The valid characters allowed for the pathname are letters, digits, and the following special characters: - _ . /
Sybase Instance	This field contains by default the name of the first Sybase instance found on the system, for which no LifeKeeper hierarchy exists. The drop down list shows other Sybase instances that may be available on your LifeKeeper server.

Sybase Backup Server	This field is used to specify the Sybase Backup server for the specified Adaptive Server instance. This Sybase Backup will be placed under LifeKeeper protection. The user may select 'none' if the Sybase Backup Server does not need to be included under LifeKeeper protection.
Sybase Monitor Server	This field is used to specify the Sybase Monitor server for the specified Adaptive Server instance. This Sybase Monitor will be placed under LifeKeeper protection. The user may select 'none' if the Sybase Monitor Server does not need to be included under LifeKeeper protection.
Sybase ASE Database Tag	This is a unique tag name for the new Sybase ASE database resource on the primary server. The default tag name consists of the word sybase followed by the name of the Adaptive Server instance. You may type in another unique tag name. The valid characters allowed for the tag are letters, digits, and the following special characters: - _ . /

4. Click **Next**. The *Create Resource Wizard* will then create your Sybase ASE resource hierarchy. LifeKeeper will validate the data entered. If LifeKeeper detects a problem, an error message will appear in the information box.
5. You should see a message indicating that you have successfully created a Sybase ASE resource hierarchy, and you must extend that hierarchy to another server in your cluster to achieve failover protection. Click **Next**.
6. Click **Continue**. LifeKeeper will then launch the *Pre-extend Wizard*. Refer to Step 2 under [Extending a Sybase ASE Resource Hierarchy](#) for details on how to extend your resource hierarchy to another server.

Extending a Sybase ASE Resource Hierarchy

This operation can be started from the **Edit** menu, or initiated automatically upon completing the **Create Resource Hierarchy** option, in which case you should refer to Step 2 below.

1. On the **Edit** menu, select **Resource**, then **Extend Resource Hierarchy**. The Pre-Extend Wizard appears. If you are unfamiliar with the Extend operation, click **Next**. If you are familiar with the LifeKeeper **Extend Resource Hierarchy** defaults and want to bypass the prompts for input/confirmation, click **Accept Defaults**.
2. The *Pre-Extend Wizard* will prompt you to enter the following information.
Note: The first two fields appear only if you initiated the Extend from the **Edit** menu.

Field	Tips
Template Server	Select the server where your Sybase ASE resource is currently in service.
Tag to Extend	Select the Sybase ASE resource you wish to extend.
Target Server	Enter or select the server you are extending <i>to</i> .
Switchback Type	This determines how the Sybase ASE resource will be switched back to the primary server after it comes in-service (active) on the backup server following a failover. You can choose either intelligent or automatic. The switchback type can be changed later, if desired, from the General tab of the Resource Properties dialog box. Note: Remember that the switchback strategy must match that of the dependent resources to be used by the Sybase ASE resource.
Template Priority	Select or enter a Template Priority . This is the priority for the Sybase ASE hierarchy on the server where it is currently in service. Any unused priority value from 1 to 999 is valid, where a lower number means a higher priority (1=highest). The extend process will reject any priority for this hierarchy that is already in use by another system. The default value is recommended. Note: This selection will appear only for the initial extend of the hierarchy.
Target Priority	This is the priority for the new extended Sybase ASE hierarchy relative to equivalent hierarchies on other servers. Any unused priority value from 1 to 999 is valid, indicating a server's priority in the cascading failover sequence for the resource. Note that LifeKeeper assigns the number "1" to the server on which the hierarchy is created by default. The priorities need not be consecutive, but no two servers can have the same priority for a given resource.

3. After receiving the message that the pre-extend checks were successful, click **Next**.

4. Depending upon the hierarchy being extended, LifeKeeper will display a series of information boxes showing the Resource Tags to be extended, some of which cannot be edited.
5. The Extend Wizard will prompt you to enter the following information.

Sybase ASE Install Directory	This field contains by default the Sybase ASE install path of the Template Resource. The valid Sybase ASE installation path should be specified. The valid characters allowed for the pathname are letters, digits, and the following special characters: - _ . /
Sybase ASE Database Tag	This is a unique tag name for the new Sybase ASE database resource on the primary server. The default tag name consists of the word sybase followed by the name of the Adaptive Server instance. You may type in another unique tag name. The valid characters allowed for the tag are letters, digits, and the following special characters: - _ . /

6. After receiving the message "Hierarchy extend operations completed" click **Next Server** to extend the hierarchy to another server, or click **Finish** if there are no other extend operations to perform.
7. After receiving the message "Hierarchy Verification Finished", click **Done**.

Unextending a Sybase ASE Resource Hierarchy

To remove a resource hierarchy from a single server in the LifeKeeper cluster, do the following:

1. On the **Edit** menu, select **Resource**, then **Unextend Resource Hierarchy**.
2. Select the **Target Server** where you want to unextend the Sybase ASE resource. It cannot be the server where the resource is currently in service. (This dialog box will not appear if you selected the Unextend task by right clicking on a resource instance in the right pane.) Click **Next**.
3. Select the Sybase ASE hierarchy to unextend and click **Next**. (This dialog will not appear if you selected the Unextend task by right clicking on a resource instance in either pane).
4. An information box appears confirming the target server and the Sybase ASE resource hierarchy you have chosen to unextend. Click **Unextend**.
5. Another information box appears confirming that the Sybase ASE resource was unextended successfully. Click **Done** to exit the Unextend Resource Hierarchy menu selection.

Deleting a Sybase ASE Resource Hierarchy

To delete a Sybase ASE resource from **all** servers in your LifeKeeper configuration, complete the following steps:

1. On the **Edit** menu, select **Resource**, then **Delete Resource Hierarchy**.

2. Select the name of the **Target Server** where you will be deleting your Sybase ASE resource hierarchy.

Note: If you selected the Delete Resource task by right clicking from either the left pane on a global resource or the right pane on an individual resource instance, this dialog will not appear.

3. Select the **Hierarchy to Delete**. (This dialog will not appear if you selected the Delete Resource task by right clicking on a resource instance in the left or right pane.) Click **Next**.
4. An information box appears confirming your selection of the target server and the hierarchy you have selected to delete. Click **Next**.
5. Another information box appears confirming that the Sybase ASE resource was deleted successfully.
6. Click **Done** to exit.

Testing Your Resource Hierarchy

You can test your Sybase ASE resource hierarchy by initiating a manual switchover that will simulate a failover of the resource instance from the primary server to a backup server.

Performing a Manual Switchover from the LifeKeeper GUI

You can initiate a manual switchover from the LifeKeeper GUI by selecting **Edit, Resource, and In Service**. For example, an in-service request executed on a backup server causes the Sybase ASE resource hierarchy to be placed in service on the backup server and taken out-of-service on the primary server. At this point, the original backup server is now the primary server and original primary server has now become the backup server.

If you execute the **Out of Service** request, the resource hierarchy is taken out-of-service without bringing it in service on the other server.

Important: After bringing your resource hierarchy in service on the backup server you should attempt to connect to the databases, especially when using raw devices as device spaces. This is necessary to ensure that all disk partitions are visible on the backup servers and the raw bindings are being established correctly.

If the raw bindings have not been established on the backup servers, it is most likely caused by the fact that new partitions were created on the primary server and added to the configuration, but the partition tables have not yet been updated on the backup servers.

The solution is to reboot the backup servers so that the partition tables are updated correctly.

Resource Hierarchy Administration

The following tasks may be required after your resource hierarchies have been created.

Modifying protection for the Sybase Backup Server

The Sybase Backup Server is an Open Server-based application that manages all database backups (dump) and restores (load) operations for Adaptive Server. The Sybase Backup Server can be protected by the LifeKeeper Sybase ASE resource hierarchy during the resource creation, or added to the LifeKeeper protection after the resource hierarchy creation. In addition, the Sybase Backup Server can be removed from LifeKeeper protection after the hierarchy has been created.

Adding a Sybase Backup Server

To add a Sybase Backup Server to an existing Sybase ASE resource hierarchy, the Sybase `srvbuild` or other configuration utility must have created one.

1. On the **Edit** menu, select **Resource**, select **Properties**. A **Resource Properties** wizard will appear.
2. Select the resource tag from the **Select Resource** pull down. This is the resource tag for the LifeKeeper protected Sybase ASE resource to modify.
3. Select the LifeKeeper Server from the **Select Server for Resource** pull down. This will be the server to update the Sybase ASE resource instance on. If changes are required on more than one LifeKeeper server, then this process should be repeated for each server in the cluster.
4. Select the **Resource Configuration** button on the **Resource Properties** page. This will launch a Reconfiguration wizard for the protected resource selected in step 3. The first screen of the wizard will display the current configuration settings for the resource under LifeKeeper protection. Select **Next**.
5. If a valid Sybase Backup Server exists on the specified server, the next screen will display a pull down for the **Sybase Backup Server** to add or remove. Select the Sybase Backup Server to add from the list. Select **Next**. Note: For Sybase ASE installations where the Sybase software is installed on shared storage, the file system containing the installation must be in-service on the server where the reconfiguration will take place.
6. If a valid Sybase Monitor Server exists, the next screen will allow you to configure it now. Refer to [Modifying Protection for the Sybase Monitor Server](#) for considerations regarding modifying the Monitor Server protection.
7. Select **Reconfigure**. If any errors are displayed they must be corrected before proceeding. Otherwise, select **Done**.
8. Any Sybase Backup Server configuration file paths, or associated database devices should be manually protected with a LifeKeeper file system resource, and made a dependent of the parent resource hierarchy.
9. The virtual IP address associated with the Sybase Backup Server must be made a dependent of the parent resource hierarchy. To find the associated IP address, look for the master and query lines following the Sybase Backup Server name in the interfaces file.

Removing a Sybase Backup Server

The following steps outline the process for removing a Sybase Backup Server from an existing Sybase ASE resource hierarchy.

1. On the **Edit** menu, select **Resource**, select **Properties**. A **Resource Properties** wizard will appear.
2. Select the resource tag from the **Select Resource** pull down. This is the resource tag for the LifeKeeper protected Sybase ASE resource to modify.
3. Select the LifeKeeper Server from the **Select Server for Resource** pull down. This will be the server to update the Sybase ASE resource instance on. If changes are required on more than one LifeKeeper server, then this process should be repeated for each server in the cluster.
4. Select the **Resource Configuration** button on the **Resource Properties** page. This will launch a Reconfiguration wizard for the protected resource selected in step 3. The first screen of the wizard will display the current configuration settings for the resource under LifeKeeper protection. Select **Next**.
5. If a valid Sybase Backup Server exists on the specified server, the next screen will display a pull down for the **Sybase Backup Server** to add or remove. Select 'none' from the list to remove protection for the Sybase Backup Server. Select **Next**.
6. If a valid Sybase Monitor Server exists, the next screen will allow you to configure it now. Refer to [Modifying Protection for the Sybase Monitor Server](#) for considerations regarding modifying the Monitor Server protection.
7. Select **Reconfigure**. If any errors are displayed they must be corrected before proceeding. Otherwise, select **Done**.
8. Any Sybase Backup Server configuration file paths, or associated database devices that are no longer in use should be removed from the Sybase ASE resource dependency and deleted from LifeKeeper.
9. Any Sybase Backup Server virtual IP resources that are no longer in use should be removed from the Sybase ASE resource dependency and deleted from LifeKeeper.

Modifying Protection for the Sybase Monitor Server

The Monitor Server is a separate server from the database server that monitors the Adaptive Server. The Monitor Server can provide real time or historical data to client applications. The Sybase Monitor Server can be protected by the LifeKeeper Sybase ASE resource hierarchy during the resource creation, or added to the LifeKeeper protection after the resource hierarchy creation. In addition, the Sybase Monitor Server can be removed from LifeKeeper protection after the hierarchy has been created.

Adding a Sybase Monitor Server

To add a Sybase Monitor Server to an existing Sybase ASE resource hierarchy, the Sybase `srvbuild` or other configuration utility must have created one.

1. On the **Edit** menu, select **Resource**, select **Properties**. A **Resource Properties** wizard will appear.

2. Select the resource tag from the **Select Resource** pull down. This is the resource tag for the LifeKeeper protected Sybase ASE resource to modify.
3. Select the LifeKeeper Server from the **Select Server for Resource** pull down. This will be the server to update the Sybase ASE resource instance on. If changes are required on more than one LifeKeeper server, then this process should be repeated for each server in the cluster.
4. Select the **Resource Configuration** button on the **Resource Properties** page. This will launch a Reconfiguration wizard for the protected resource selected in step 3. The first screen of the wizard will display the current configuration settings for the resource under LifeKeeper protection. Select **Next**.
5. If a valid Sybase Backup Server exists, the next screen will allow you to configure it now. Refer to [Modifying Protection for the Sybase Backup Server](#) for considerations regarding modifying the Backup Server protection
6. If a valid Sybase Monitor Server exists on the specified server, the next screen will display a pull down for the **Sybase Monitor Server** to add or remove. Select the Sybase Monitor Server to add from the list. Select **Next**. Note: For Sybase ASE installations where the Sybase software is installed on shared storage, the file system containing the installation must be in-service on the server where the reconfiguration will take place.
7. Select **Reconfigure**. If any errors are displayed they must be corrected before proceeding. Otherwise, select **Done**.
8. Any Sybase Monitor Server configuration file paths, or associated database devices should be manual protected with a LifeKeeper file system resource, and made a dependent of the parent Sybase ASE resource hierarchy.
9. The virtual IP address associated with the Sybase Monitor Server must be made a dependent of the parent Sybase ASE resource hierarchy. To find the associated IP address, look for the master and query lines following the Sybase Monitor Server name in the interfaces file.

Removing a Sybase Monitor Server

The following steps outline the process for removing a Sybase Monitor Server from an existing Sybase ASE resource hierarchy.

1. On the **Edit** menu, select **Resource**, select **Properties**. A **Resource Properties** wizard will appear.
2. Select the resource tag from the **Select Resource** pull down. This is the resource tag for the LifeKeeper protected Sybase ASE resource to modify.
3. Select the LifeKeeper Server from the **Select Server for Resource** pull down. This will be the server to update the Sybase ASE resource instance on. If changes are required on more than one LifeKeeper server, then this process should be repeated for each server in the cluster.
4. Select the **Resource Configuration** button on the **Resource Properties** page. This will launch a Reconfiguration wizard for the protected resource selected in step 3. The first screen of the wizard will display the current configuration settings for the resource under LifeKeeper protection. Select **Next**.

5. If a valid Sybase Backup Server exists, the next screen will allow you to configure it now. Refer to [Modifying Protection for the Sybase Backup Server](#) for considerations regarding modifying the Backup Server protection
6. If a valid Sybase Monitor Server exists on the specified server, the next screen will display a pull down for the **Sybase Monitor Server** to add or remove. Select 'none' from the list to remove protection for the Sybase **Monitor Server**. Select **Next**.
7. Select **Reconfigure**. If any errors are displayed they must be corrected before proceeding. Otherwise, select **Done**.
8. Any Sybase Monitor Server configuration file paths, or associated database devices that are no longer in use should be removed from the Sybase ASE resource dependency and deleted from LifeKeeper.
9. Any Sybase Monitor Server virtual IP resources that are no longer in use should be removed from the Sybase ASE resource dependency and deleted from LifeKeeper.

Updating Parameters

When database parameters are updated for a Sybase ASE instance it is necessary to check that all changes will allow the instance to function on all LifeKeeper servers in the cluster. If changes require the addition or deletion of LifeKeeper resources, such as file systems, raw devices, or virtual IP addresses these must be added manually and made a dependency of the parent Sybase ASE resource hierarchy.

Troubleshooting

Sybase ASE Recovery Kit Error Messages

114000	Usage: %s
114001	The Sybase Install Directory cannot be empty. ACTION: Please specify a value for this field.
114002	The path %s is not a valid directory.
114003	The Sybase Product was not found in the directory %s on server %s. ACTION: Verify that a supported version of Sybase is installed in the specified location.
114004	The specified instance %s is not a valid Sybase ASE Server on %s.
114005	Unable to verify that the Sybase ASE Server %s is running.
114006	The Sybase Monitor Server %s will be protected.
114007	The Sybase Backup Server %s will be protected.
114008	The Sybase ASE Server %s is already under LifeKeeper protection on %s.
114009	An unknown error has occurred in utility %s on server %s. ACTION: View the LifeKeeper logs for details and retry the operation.
114010	Unable to get the version for the Sybase Server %s installed under %s on %s.
114011	The device %s for Sybase ASE Server %s is not a valid device.
114012	An error has occurred while trying to obtain the devices for Sybase ASE Server %s.
114013	Unable to create raw resource hierarchy for %s.
114014	Unable to create file system resource hierarchy for %s.
114015	The path %s is not on a shared file system.
114016	Unable to create resource dependency for parent %s and child %s.
114017	Information: LifeKeeper will not protect the path %s because it is not located on a shared file system.
114018	Unable to get the owner for the Sybase ASE Server %s installed under %s on %s.
114019	Unable to open file %s on server %s due to error %s.
114020	There are no hosts defined for the Sybase ASE Server %s in the file %s.
114021	There are no ports defined for the Sybase ASE Server %s in the file %s.
114022	The specified host name %s defined for the Sybase ASE Server %s in the file %s cannot be resolved.
114023	Unable to detect the host and ports for the Sybase ASE Server %s.
114024	A LifeKeeper resource hierarchy does not exist for the IP address %s on server %s. ACTION: Create a LifeKeeper resource hierarchy for the specified IP address
114025	The values specified for the target and the template servers are the same. ACTION: Please specify the correct values for the target and template servers.
114026	The system user %s does not exist on the server %s.
114027	The group id for user %s is not the same on template server %s and target server %s.
114028	The user id for user %s is not the same on template server %s and target server %s.
114029	There are no IP dependent resources defined for the Sybase resource %s on %s. ACTION: Create the required dependent IP resource hierarchy.
114030	The interfaces defined for Sybase ASE Server %s differ on template server %s and target server %s
114031	The ports defined for Sybase ASE Server %s differ on template server %s and target server %s
114032	The port %s used by the Sybase resource hierarchy %s on the server %s is in use by another application on server %s.
114033	The startup of the Sybase ASE Server(s) on %s failed for the following Sybase ASE Server(s): %s.

Troubleshooting

- 114034 Unable to stop the Sybase ASE Server(s) %s on %s.
- 114035 The Sybase ASE resource hierarchy %s does not contain any valid gen/filesys or scsi/raw resource dependents on server %s.
ACTION: The hierarchy does not contain any valid dependents, you must delete and recreate the hierarchy.
- 114036 There are no Sybase ASE Servers available for protection with LifeKeeper.
- 114037 Unable to obtain the pid of the backupserver process corresponding to instance %s.
- 114038 The pid detected for Sybase Backup Server %s in the LifeKeeper pidfile %s.LK on server %s exists in another LifeKeeper pidfile on this server.
ACTION: The duplicate pid entry in the pid files should be resolved. The pid file for the instance that is not running should be removed.
- 114039 Unable to update the resource instance %s on server %s.
- 114040 The update of the resource instance %s failed on server %s. All attempts to rollback the instance information field have failed. **ACTION:** Manual intervention is required.
- 114041 The interfaces file %s on %s contains an invalid comment line. **ACTION:** Please correct the interfaces file to remove any comment lines.
- 114042 One or more of the Sybase ASE Servers is missing from the file %s.
- 114043 The file %s does not exist on server %s.
- 114044 The reconfiguration of the Sybase ASE resource hierarchy %s on server %s was successful
- 114045 The update of the resource instance %s failed on server %s. The instance information field has not been modified.
ACTION: Retry the reconfiguration operation
- 114046 The home directory for user %s is not the same on template server %s and target server %s
- 114047 The file %s on server %s is a link that does not resolve to a dependent shared resource on the template server %s.
- 114048 The link %s and its resolved path %s are not on a protected shared filesystem.

Appendix

Creating Device Spaces using Raw I/O

Requirements

In order to use the Sybase ASE Recovery Kit with raw I/O, the following requirements must be met:

- The Linux OS must support raw I/O devices. For most distributions this support was included in the 2.4 kernel, but there are some distributions that support raw I/O on a 2.2 kernel.
- All raw I/O devices must be bound to a shared disk partition. The number of device spaces (devspaces) that will be located on raw I/O devices determines the exact number of raw devices and shared disk partitions required. Refer to the *Installation Guide Adaptive Server for Linux* for guidelines for creating database devices on raw devices.
- The version of the Sybase ASE software must support the use of raw I/O devices.

Naming Conventions

The naming of raw devices and controller varies by Linux distribution.

- On Red Hat the device name is `/dev/raw/raw<number>` and the controller is `/dev/rawctl`
- On SuSE SLES 7 versions, the name of the device is `/dev/raw<number>` and the controller is `/dev/raw`
- On SuSE SLES 8 versions the device name is `/dev/raw/raw<number>` and the controller is `/dev/rawctl`

Raw I/O Setup Steps

1. Select a shared disk partition of appropriate size for the Sybase ASE device space.
2. Bind an unused raw device node to this partition. Since this needs to be done every time the machine is rebooted, and requires root access, you may want to add the raw bindings to a system initialization file (i.e. `rc.local` or `boot.local`). **These bindings must be removed from the file once the hierarchy is under LifeKeeper protection.** LifeKeeper will re-establish the raw bindings for raw I/O devices that are under LifeKeeper protection. Use the command `raw -qa` to see which raw device nodes are already in use. For example:

```
# raw -qa
# raw /dev/raw/raw1 /dev/sda1
```

3. Set global read permissions on both the raw device controller (`/dev/rawctl` or `/dev/raw`), and the disk partition on all servers that will protect the database instance.

```
# chmod a+r /dev/rawctl (or chmod a+r /dev/raw )
```

4. Set group and user read/write permissions on the raw device on all servers that will protect the database instance

```
# chmod 664 /dev/raw/raw1
```

5. Change the owner of the raw device to the Sybase ASE owner for the given database instance on all servers that will protect the database instance.

```
# chown -R sybase:sybase /dev/raw/raw1
```

6. Refer to the *Installation Guide Adaptive Server for Linux* for information on adding the raw device to the database server(s).

Adding a Device Space after Creating Hierarchy

If a database device is added on a raw I/O device or shared file system *after* the Sybase ASE hierarchy has been created in LifeKeeper, you must manually create a resource hierarchy for the raw device or file system via the LifeKeeper GUI. The newly created resource hierarchy must then be made a dependent (child) of the Sybase ASE resource hierarchy.

Creating Links for ASE and OCS

The LifeKeeper for Linux Sybase ASE Recovery Kit requires that the path `$$SYBASE/ASE-<version>` be symbolically linked to `$$SYBASE/ASE`. In addition, the path `$$SYBASE/OCS-<version>` must be symbolically linked to `$$SYBASE/OCS`. The LifeKeeper for Linux Sybase ASE Recovery Kit uses these links to access various Sybase utilities and files. To create the links follow the steps below.

1. From the command line change directories into the `$$SYBASE` directory.

Example:

```
server1 # cd $$SYBASE
```

```
server1 # pwd
```

```
/opt/sybase-12.5
```

2. Locate the `ASE-<version>` directory

Example:

```
server1 # ls -ld ASE*
```

```
drwxrwxr-x 16 sybase sybase 4096 Nov 18 09:08 ASE-12_5
```

```
lrwxrwxrwx 1 sybase sybase 8 Nov 17 11:35 ASEP -> ASEP-1_0
```

```
drwxrwxr-x 4 sybase sybase 4096 Nov 17 11:35 ASEP-1_0
```

Note: If a link already exists between `ASE-12_5` and `ASE`, proceed to step 5.

3. Verify that the `ASE-<version>` directory contains the `bin/srvbuild` utility.

Example:

```
server1 # ls ASE-12_5/bin/srvbuild
```

```
srvbuild
```

Note: If a no such file or directory error occurs, then you have chosen the wrong path.

- From the command line create a link between the identified ASE-<version> directory and ASE.

Example:

```
server1 # pwd
/opt/sybase-12.5
server1 # ln -s ASE-12_5 ASE
```

- Verify the link was properly created.

Example:

```
server1 # ls -ld ASE*
lrwxrwxrwx 1 sybase sybase 8 Nov 17 11:20 ASE -> ASE-12_5
drwxrwxr-x 16 sybase sybase 4096 Nov 18 09:08 ASE-12_5
lrwxrwxrwx 1 sybase sybase 8 Nov 17 11:35 ASEP -> ASEP-1_0
drwxrwxr-x 4 sybase sybase 4096 Nov 17 11:35 ASEP-1_0
server1 # ls ASE/bin/srvbuild
srvbuild
```

- From the command line change directories into the \$SYBASE directory.

Example:

```
server1 # cd $SYBASE
server1 # pwd
/opt/sybase-12.5
```

- Locate the OCS-<version> directory

Example:

```
server1 # ls -ld OCS*
drwxrwxr-x 16 sybase sybase 4096 Nov 18 09:08 OCS-12_5
```

Note: If a link already exists between OCS-12_5 and OCS, proceed to step 5.

- Verify that the OCS-<version> directory contains the bin/isql utility.

Example:

```
server1 # ls OCS-12_5/bin/isql
isql
```

Note: If a no such file or directory error occurs, then you have chosen the wrong path.

- From the command line create a link between the identified OCS-<version> directory and OCS.

Example:

```
server1 # pwd
/opt/sybase-12.5
server1 # ln -s OCS-12_5 OCS
```

- Verify the link was properly created.

Appendix

Example:

```
server1 # ls -ld OCS*
```

```
lrwxrwxrwx  1 sybase sybase      8 Nov 17 11:20 OCS -> OCS-12_5
```

```
drwxrwxr-x 16 sybase sybase    4096 Nov 18 09:08 OCS-12_5
```

```
server1 # ls ASE/bin/isql
```

```
isql
```